Braq Cube® 4C & 4CA DESIGNED BY THE BLACK TANK



Gorgeous Palette of Colors

Braq Cube 4C and 4CA fixtures pack an unprecedented 100 watts of output into just a 5 inch cube! Despite its surprisingly small size, the Braq pushes out more than enough light to replace conventional wash lights on stage, film sets or commercial architecture.

The best-in-class quad-chip emitters inside the Braq Cube RGBW 4C and the RGBA 4CA produce a gorgeous palette of saturated, mid-tone and pale tint colors. Thanks to the high quality of the emitters, the 4C and 4CA can also mix an attractive, full spectrum white light in warm and cool color temperatures - not the unflattering compromise found in other color-mixing LED lights.


The Braq Cube 4CA features a unique, phosphor-converted amber emitter – not found in any other RGBA fixture this size. This enables it to produce an expanded palette of saturated colors and rich, warm-tones of full-spectrum white light.



Smart programming in the Braq Cube 4C & 4CA includes a stand-alone color wash mode and allows multiple units to be easily slaved together, synchronized and off-set using self-generated DMX for color chases and other dynamic lighting patterns without a console. Use it alone, configured in strips & arrays or build it directly into the set or architecture for virtually any application needing colored light, including: stage productions, broadcast studios, bars and casinos, up-scale lobbies and retail stores.

WHAT'S IN THE BOX

Braq Cube Set of Symmetrical Spread Lenses Powercon (not included in no cord version)



KEY FEATURES

- RGBW 4C and the RGBA 4CA produce a broad palette of different hues, as well as an attractive, full spectrum white light in warm and cool color temperatures
- 4C & 4CA single chip optic casts fringe-free shadows
- Unique patented (US Patent No. 8,767,398) heat management system packs the most lumens into the smallest form factor
- No expensive power supply or ballasts direct to mains power 90-240VAC 50/60 Hz
- Over 20 luminaires on a single 20A circuit
- Flicker-free dimming in 8 or 16 bit resolution
- Intuitive touch panel full-text interface for manual control
- Easily installed on standard line-voltage lighting track with optional yoke assembly, including full DMX track options
- Full assortment of spot, medium and wide lenses included
- Novel "filament mode" mimics the delayed blackout glow of incandescent fixtures

Braq Cube® 4C & 4CA DESIGNED BY THE BLACK TANK



SPECIFICATIONS

Output:

Color Range:

Input Voltage: 90 - 240 VAC 50/60Hz Humidity: 0 - 95% non-condensing

Power Consumption: 100 Watt at maximum output 5 in x 5 in x 5.3 in Dimensions:

(127 mm x 127 mm x 135 mm) Power Input: Neutrik Powercon input and pass-thru

Weight: 3.5 lbs (1.6 kg) LED: 7 x 12W Osram Multi-chip

Housing: Powder Coated Aluminum Extrusion Lumen Maintenance: 80,000 hours B50 L70 at 45° C

(1/8" wall) (LM-79-08 Standard)

Approvals: FCC Class A Radiated and Conducted DMX 5-pin XLR male, 5-pin XLR Female Data:

ETL / UL Standards 1573 and 8750 cETL / CSA C22.2 #166-M1983

4CA: 1710 lumens CE / IP20 Rated

4CA: Red/Green/Blue/Amber Operation: DMX: 8 or 16 bit DMX512/Manual: Full Text LCD

4C: Red/Green/Blue/White (6500K)

Operating Temp.: -13° to 113° F (-20° to 45° C)

4C: 1800 lumens









| Braq Cube® 4C & 4CA | | | | |
|---------------------|--------------------------------------|----------------|---------------------------------------|--|
| Item Code | Description | Item Code | Description | |
| 515 90100 1014 | Braq Cube 4C - Black w/Power Cord | 515 90100 1040 | Braq Cube 4CA – Black w/Power Cord | |
| 515 90100 2014 | Braq Cube 4C - White w/Power Cord | 515 90100 2040 | Braq Cube 4CA – White w/Power Cord | |
| 515 90100 1114 | Braq Cube 4C – Black (no power cord) | 515 90100 1140 | Braq Cube 4CA – Black (no power cord) | |
| 515 90100 2114 | Braq Cube 4C – White (no power cord) | 515 90100 2140 | Braq Cube 4CA – White (no power cord) | |

| Braq Cube® Accessories | | | | |
|------------------------|----------------------------|----------------|---|--|
| Item Code | Description | Item Code | Description | |
| 515 91032 0000 | Accessory Holder - Black | 515 91010 0120 | 20° Symmetrical Spread Lens | |
| 515 91032 0004 | Accessory Holder - White | 515 91010 0140 | 40° Symmetrical Spread Lens | |
| 515 91032 0001 | Top Hat – Black | 515 91010 0160 | 60° Symmetrical Spread Lens | |
| 515 91032 0006 | Top Hat - White | 515 91010 0003 | Set of Three Symmetrical Spread Lenses | |
| 515 91032 0002 | Egg Crate Louver – Black | 515 91012 3005 | 30° x 5° Asymmetrical Lens | |
| 515 91032 0005 | Egg Crate Louver – White | 515 91012 6010 | 60° x 10° Asymmetrical Lens | |
| 515 91032 0003 | Barn Doors - Black | 515 91012 7545 | 75° x 45° Asymmetrical Lens | |
| 515 91032 0008 | Barn Doors - White | 515 91010 0004 | Set of Three Asymmetrical Spread Lenses | |
| 515 91023 0000 | Double-Yoke – Black | 515 91015 0005 | Miro/Braq Powercon Cord w/Plug | |
| 515 91023 0001 | Double-Yoke - White | 515 91017 0005 | Miro/Braq Powercon Cord w/Inline Switch | |
| 515911100009 | Braq Track Adaptor – Black | 515 91017 0001 | Powercon Pass-Thru Cord | |
| 515911100008 | Braq Track Adaptor - White | | | |